

- API SG/CD
- ISIRI 1342, 3785

ECCO 
Reduce Fuel Consumption
8000

PRODUCT SPECIFICATIONS :

| Specifications | SAE grade | | | Test method ASTM |
|-----------------------------------|-----------------|-----------------|-----------------|---------------------|
| | 20W/50 | 15W/40 | 10W/40 | |
| Kinematic Viscosity @ 100° C, cSt | 19 | 15.3 | 15.3 | D 445 |
| Viscosity Index | ≥ 120 | ≥ 135 | ≥ 150 | D 2270 |
| Flash Point, °C | ≥ 220 | ≥ 210 | ≥ 210 | D 92 |
| Pour Point, °C | ≤ -24 | ≤ -27 | ≤ -33 | D 97 |
| Volatility, %W | ≤ 10 | ≤ 13 | ≤ 15 | D 5800 |
| Specific Gravity @ 15°C, Kg/m³ | 890 | 885 | 870 | D 1298 |
| CCS, cP | -15°C ≤ 9500 | -20°C ≤ 7000 | -25°C ≤ 7000 | D 5293 |

Specifications

- Use of hydrogenated base oil for thermal stability increasing and resistance against oxidation
- Including premium high viscosity index group III base oil for thermal stability increasing and resistance against oxidation (only for SAE 10W/40)
- Good anti-oxidation and thermal stability
- Cleaning property in order to decrease of deposits of combustion and oxidation
- Anti-wear property in order to control of engine parts erosion
- Neutralization property of acids due to oxidation and combustion in order to prevent of engine parts corrosion
- Good protection of engine under any weather conditions
- Increasing of life time and engine power
- Easy engine starting and quick lubricating in low temperatures
- Good shear stability of product to keeping viscosity during consumption
- Good capability in elimination of extra heat from engine to protect of parts metallurgical structures
- Desirable control of oil consumption and cost reduction



Head office : 2224 Vahdat Avenue, Suite
1407, Tehran, Iran
Factory: 11 Vahdat Avenue, Taleghani, Qazvin
Petro co. Iran, (+9821) 88100505
www.eccolubricants.com

شرکت پترو صنعت ایران


ECCO 
8000



شرکت پترو صنعت ایران



Ecco V 8000

ECCO  **8000** Engine oil is manufactured of high grade mineral base oil extracted of lube cut refining of crude oil and updated additives according to Vulcan Petrochem Ltd formula-tion to use in all seasons and weather conditions.

Usage

Suitable for passenger cars such as Pride (Nasim, Saba, 141, 111, 132) , Peugeot Roa, Peugeot RD, Rio, Renault PK, Nissan Patrol, Proton Wira, Pazhan, Land-Rover, MVM and all of gasoline vehicles designed until 1993 and super charged diesel when the above performance levels with grades SAE 10W/40, 15W/40 and 20W/50 are recommended by the manufacturer.

Packaging:

This product is offered in 1 & 4 Liters gallons

