

- API S/CF
- ISIRI 9186, 11378

**ECCO V**  
Reduces Engine Noise  
**16000**

PRODUCT SPECIFICATIONS :

specifications	SAE grade 20W/50	15W40	ASTM Test method
Kinematic Viscosity @ 100° C, cSt	19	15.5	D 445
Viscosity Index	≥ 120	≥ 135	D 2270
Flash Point, °C	≥ 210	≥ 220	D 92
Pour Point, °C	≤ -27	≤ -24	D 97
Volatility, %W	≤ 13	≤ 15	D 5800
Specific Gravity @ 15°C, Kg/m³	890	885	D 1298
CCS, cP	-15°C ≤ 9500	-20°C ≤ 7000	D 5293

Specifications :

- Use of hydrogenated base oil for thermal stability increasing and resistance against oxidation
- Desirable anti-oxidation and thermal stability
- Cleaning property in order to decrease of deposits of combustion and oxidation
- Anti-wear property in order to control of engine parts erosion
- Desirable property of acids due to oxidation and combustion in order to prevent of engine parts corrosion
- Desirable protection of engine under any weather conditions
- Increasing of life time and engine power desirably
- Easy engine start and quick lubricating desirably in low temperatures
- Desirable shear stability of product to keeping viscosity during consumption
- Desirable capability in elimination of extra heat from engine to protect of parts metallurgical structures
- Desirable control of oil consumption and cost reduction



Head office : 2224 Vahed Avenue, Suite  
1407, Tehran, Iran  
Factory : 11 Vahed Street, Tashan, Qazvin  
P.O. Box : 141 (9621) 88100050-5  
www.eccodirect.com



**ECCO V**  
**16000**



محلول موتور



Ecco V 16000

**ECCO V 16000** Engine oil is manufactured of high viscosity index paraffinic hydro-finished base oil extracted of lube cut refining of crude oil and adequate additives according to Vulcan Petrochem Ltd formulation to use in all seasons and weather conditions.

Usage :

Suitable for passenger cars such as Mazda 323, Toyota Prado, Land Cruiser (before 2009), Volkswagen Gol, Pars ELX, Hyundai Avante, J5, Geely, JAC and other of gasoline vehicles designed until 2004 and super charged diesel when the above performance levels with grades SAE 20W/50 and 15W40 are recommended by the manufacturer.

Packaging:

This product is offered in 1 & 4 Liters gallons

