

- API CC/SC
- ISIRI 585

## **ECCO**✓ High Quality Diesel Engine Oil **NICOL CC 25W50**

Specifications	SAE grade 25W50	ASTM Test method
Kinematic Viscosity @ 100 °C, cSt	19.5	D 445
Viscosity Index	≥ 100	D 2270
Flash Point, °C	≥ 220	D 92
Pour Point, °C	≤ -24	D 97
TBN, mg KOH/gr	≥ 10	D 2896
Specific Gravity @ 15°C, Kg/m³	890	D 1298
CCS @ -10°C, cP	≤ 13000	D 5293

### Specifications

- Use of hydrogenated base oil to increase anti-oxidation and thermal stability
- Anti-wear property and prevention of engine parts erosion
- High cleaning and dispersion effects in order to decrease of soot and precipitates from engine surface
- Proper alkalization in order to prevent of unfavorable effects of produced acids due to inner combustion and therefore long engine life
- Stability of oil viscosity in high operating temperatures
- Reduction of fuel consumption



Head office : 2224 Vahed-Ar Avenue, Suite  
1407, Tehran, Iran  
Factory : 11 Vahed Street, Tabriz, Qazvin  
Province, Iran. (+9621) 88100650-5  
[www.eccodirect.com](http://www.eccodirect.com)



**ECCO**✓  
High Quality Diesel Engine Oil  
**NICOL CC 25W50**



### ECCO✓ NICOL

**ECCO✓ NICOL** engine oil is produced of high viscosity index paraffinic hydro-finished base oil, extracted of lube cut refining of crude oil and adequate additives according to Vulcan Petrochem Ltd formulation to use in all light and heavy-duty four-stroke super and turbo charged diesel and gasoline engines in all seasons and weather conditions.

### Usage:

Suitable for all light and heavy-duty diesel and gasoline engines and road machinery, equipment used in mines, agriculture and all automobiles which the above performance levels with grade SAE 25W50 are recommended by the manufacturer.

### Packaging:

This product is offered in drum, 20 & 4 liters gallons.

