- API SM/CE
- ILSAC GF-4
- GM-DEXOS 1 ISIRI 13383, 11378



PRODUCT SPECIFICATIONS:

	SAE grade 5W40	
Kinematic Viscosity @ 100° C, cSt	15.3	D 445
Viscosity index	≥ 165	D 2270
Flash Point, °C	≥ 210	D 92
Pour Point, °C	≤ -36	D 97
Volatility, %W	≤ 15	D 5800
Specific Gravity @ 15°C, Kg/m ³	850	D 1298
CCS @ -30°C, cP	< 6600	D 5202

- . Including high viscosity index group III base oil for thermal stability increasing and resistance against oxidation
- . Excellent anti-oxidation and thermal stability
- . Cleaning property in order to decrease of deposits of combustion and oxidation
- . Excellent anti-wear property in order to control of engine parts erosion
- . Neutralization property of acids of oxidation and combustion in order to
- prevent of engine parts corrosion · Excellent protection of engine under any weather conditions
- . Increasing of life time and power of engine excellently
- . Easy engine starting and quick lubricating in low temperatures
- · Excellent shear stability of product to keeping of viscosity throughout consumption
- . Excellent capability in elimination of extra heat from engine to protect of parts metallurgical structures
- . Excellent control of oil consumption and cost reduction







EccoV Prima Gold

ECCO PRIMA GOLD engine oil is produced of full synthetic high viscosity index group III base oil and using from the best undated additives, and according to the Vulcan Petrochem. Ltd formulation to use in all seasons and weather conditions.

Suitable for passenger cars such as Nissan pickup, Maxima, Teana, Qashqai, Voleex C30, Peugeot 407, Hyundai i30, ix35, ix55, Genesis, Avante, Sonata, Veracruz, Renault Latitude, Brilliance V5, Mazda, Musso, BMW, Kia Opirus, Cerato, Carnival, Sportage, Mohave, Optima, Mitsubishi outlander, Renault Koleos, Tovota Avalon, Prado, Corolla, Land Cruizer (after 2009), Matrix, FI Cruiser, Ssang Yong Kyron, Activen, Subaro Legacy, I-MIEV and all the vehicles which above performance levels with grade SAE 5W40 are recommended by the manufacturer.

Packaging:

This product is offered in 1 & 4 Liters gallons



