

- API SM/CF
- ILSAC GF-4
- GM-DEXOS 1
- ISIRI 13383, 11378

ECCO
For Long Engine Life
PRIMA

PRODUCT SPECIFICATIONS :

Specifications	SAE grade	Test method
	10W40	ASTM
Kinematic Viscosity @ 100° C, cSt	15.3	D 445
Viscosity index	≥ 150	D 2270
Flash Point, °C	≥ 210	D 92
Pour Point, °C	≤ -33	D 97
Volatility, %W	≤ 15	D 5800
Specific Gravity @ 15°C, Kg/m³	870	D 1298
CCS @ -25°C, cP	≤ 7000	D 5293

Specifications :

- Including high viscosity index group III base oil for thermal stability increasing and resistance against oxidation
- Excellent anti-oxidation and thermal stability
- Cleaning property in order to decrease of deposits of combustion and oxidation
- Excellent anti-wear property in order to control of engine parts erosion
- Neutralization property of acids of oxidation and combustion in order to prevent of engine parts corrosion
- Excellent protection of engine under any weather conditions
- Increasing of life time and power of engine excellently
- Easy engine starting and quick lubricating in low temperatures
- Excellent shear stability of product to keeping of viscosity throughout consumption
- Excellent capability in elimination of extra heat from engine to protect of parts metallurgical structures
- Excellent control of oil consumption and cost reduction



Head office : 2224 voh-Ar Avenue, Suite
1407, Tehran, Iran
Factory : 11 voh-Ar Street, Tehran, Qazvin
Province, Iran. (+9621) 88100050-5
www.eccodatacenter.com



ECCO
PRIMA



ECCO V Prima

ECCO **PRIMA** engine oil is produced of high viscosity index group III semi synthetic base oil and using from the best updated additives, and according to the Vulcan Petrochem Ltd formulation to use in all seasons and weather conditions.

Usage:

Suitable for passenger cars such as Nissan murano, Teana, Qashqai, Peugeot 407, Hyundai i30, ix35, Genesis, Azera, Sonata, Veracruz, Kia Cerato, Carnival, Sportage, Mohave, Optima, Renault Koleos, Toyota Prado, Land Cruiser (after 2009), and all of vehicles which above performance levels with grade SAE 10W40 are recommended by the manufacturer.

Packaging:

This product is offered in 1 & 4 Liters gallons

